

5G CPE

AX5400

LTE Supported

- 4*4 MU-MIMO
- Rapid one-button pairing
- VoLTE and VoNR supported
- Speeds up to 3.2 Gbps



5G Internet

Anytime, Anywhere

Product Introduction

Xunison Hub D60 5G is a powerful 5G CPE with Wi-Fi 6 Mesh solution, low latency, and high capacity to connect more devices simultaneously.



Support 802.11 a/b/g/n/ac/ax

Latest wireless technology with backward compatibility




5G

5G LTE provides a home Wi-Fi network with low latency, high speeds, and extensive coverage.



High-Speed Wi-Fi 6

Wireless technology supporting the latest Wi-Fi standard 802.11ax including backward compatibility with legacy Wi-Fi devices.



Wi-Fi Mesh

Eliminates Wi-Fi in-home dead zones and increases Wi-Fi network coverage area.



Parental Control

Feature specifically for monitoring and controlling child's activity on the internet.



Xunison Hub D60 5G

SPECIFICATIONS

Data Range	NSA: 3.4Gbps (DL)/550Mbps (UL)
	SA: 2.4Gbps (DL)/900Mbps (UL)
	CAT19: LTE 1.6Gbps (DL)/CAT18: LTE 200Mbps (UL)
	WCDMA: 42 Mbps (DL)/5.76 Mbps (UL)
Chipset	IPQ5018+QCN6024+QCA8337
Wireless LAN	Support 802.11 a/ b/g/n /ac/ax standard
	20/40/80/160 MHz bandwidth
	Channel adaption
	MSSID + Guest network
	WPS: PBC/PIN modes
	WPA/WPA2/WPA3 security
DL MU-MIMO & OFDMA	
Wi-Fi Mesh	Wi-Fi Son/Easy MESH*
	One button pairing
Wi-Fi Antennas	Internal 2*2 2.4GHz & 4*4 5GHz antennas
	Gain: 3dBi
5G NR/LTE Antennas	Internal: 4*4 5G/LTE antennas
	LB: 2dBi
	MHB: 4dBi
	External TS9 port
Wireless Module	Auto/Manual network search
	Dual Link backup
	Traffic statistics
	VoLTE
Security	Built in firewall
	Defense of DoS ARP attacks/Port scan
	MAC Port filtering
	802.1x
Quality of Service control	802.11 e
	Classification of service flow*
	Port/VLAN/ IP rate limitation



Bracken Business Park, Bracken Rd, Sandyford Business
Park, Sandyford, Dublin, Ireland

www.xunison.com



Xunison Hub D60 5G

Network Protocols and Features	Operation modes: Bridge/Routed
	Connection modes: PPPoE/DHCP/Static
	IPv4, IPv6, IPv4/IPv6
	DHCP v4/v6 server
	Static (v4/v6) routing
	NAT/ALG/DMZ/virtual server
	ARP/ICMP/DNS proxy
	IGMP snooping and IGMP proxy*
	MLD snooping and MLD proxy*
	NTP
	VLAN
VPN: PPTP L2TP/IPSec	

Platform	CPU: Dual Core A53, 1.0 GHz
	FLASH: 128MB
	RAM: 512 MB

Physical Interface	2 x TS-9 External Antenna Ports
	1 x USB 2.0
	3 x LAN ports
	1 x WAN port
	1 x Phone port
	1 x SIM slot
	DC 12V Port

Buttons	PAIR
	RESET
	POWER

LED indicators	Wi-Fi indicator
	5G NR indicator
	4G LTE indicator
	Phone indicator
	Internet indicator
	Power indicator
	LAN port indicators



Bracken Business Park, Bracken Rd, Sandyford Business
Park, Sandyford, Dublin, Ireland

www.xunison.com



Xunison Hub D60 5G

Management	WebUI local management
	TR069 remote management
	Universal Plug and Play
	Online and Local software upgrade
Physical Specification	Operating Conditions: -10°C to 45°C
	Storage Conditions: -40°C to 70°C
	Humidity: 5% - 95%(non-condensing)
Package Includes	Xunison Hub D60 5G
	Quick Start Guide
	Power Adapter
	Ethernet Cable



Bracken Business Park, Bracken Rd, Sandyford Business
Park, Sandyford, Dublin, Ireland

www.xunison.com



Xunison Hub D60 5G

DEVICE IMAGES



DEVICE IDENTIFICATION

Brand	Xunison
Device name	Xunison Hub D60 5G
SKU	R5-NN-D4-QC-125
Part Number	R5Q-D60-1G-DB4-EU
Barcode	Not Applicable
Serial Number	Not Applicable



Bracken Business Park, Bracken Rd, Sandyford Business Park, Sandyford, Dublin, Ireland

www.xunison.com